

## PATENT ABSTRACTS OF JAPAN

引用例

Reference No. 1

(11)Publication number : 11-244098

(43)Date of publication of application : 14.09.1999

(51)Int.Cl.

A47C 27/04

A47C 27/05

A47C 27/06

(21)Application number : 10-061976

(71)Applicant : NIPPON BED SEIZO KK

(22)Date of filing : 27.02.1998

(72)Inventor : USAMI NOBUO

## (54) MATTRESS FOR BED

(57)Abstract:

**PROBLEM TO BE SOLVED:** To provide a mattress of which the number of production processes can be reduced and durability is improved by controlling an excessive deflection of side parts due to an eccentric load on edges.

**SOLUTION:** A border cushion material 2 and a border quilt 5, a top face cushion material 3 and a top face quilt 6, an underside cushion material 4 and an underside quilt 7 are respectively adhered to each other through a synthetic resin adhesive. The underside of the top face cushion material 3 and the top face of the underside cushion material 4 are respectively adhered to the top faces and the undersides of bag bodies 11 of numerous pocket coils 10 constituting a spring unit 1. The peripheral parts of the top face cushion material 3 and the underside cushion material 4 are projected from the outer periphery of the spring unit 1 by a length substantially corresponding to the thickness of the border cushion material 2 and butted with both upper and lower end faces of the border cushion material 2.

